

Maximum Performance (MaP) of PRESSURE- AND POWER-ASSIST UNAR-Compliant High-Efficiency Toilet Fixtures (HETs)

Sorted by Manufacturer

June 2009 listing

Note: Compiling this listing is a service of the U.S.-Canadian Alliance for Water Efficiency and the California Urban Water Conservation Council. All of the fixtures on this list are believed to meet the requirements of the U.S. EPA WaterSense specification for HETs, although there is no guarantee of such. Those that have been reported to be fully certified to WaterSense by recognized laboratories are identified in the WaterSense column below. NOTE: This listing is NOT the official list of the U.S. EPA's WaterSense Program. For a full description of WaterSense, go to: <http://www.epa.gov/watersense/>

MaP Test Report No. (for internal use)	Make	Model Name	Model Number	MaP Flush Performance (grams of solid waste removed from the toilet in a SINGLE flush)	Certified to the U.S. EPA WaterSense Specification for High-Efficiency Toilets	1-piece or 2-piece model	Round Front (R) or Elongated (E) bowl	ADA-Comfort Height-Right Height Bowl	Rear Discharge	Floor-Mounted (F) OR Wall-Mounted (W)	KEY:
											Flush performance (MaP score)
											350 grams to 475 grams
											500 grams and more
											NM - Not measured for Maximum Performance - these WaterSense fixtures met the minimum 350 gram waste removal threshold, however.
WS-14	American Standard	Cadet Flowise EL	2462.100: 3481.100 bowl, 4142.100 tank	NM	WS	2	E			F	
WS-14	American Standard	Cadet Flowise EL ADA	2467.100: 3483.100 bowl, 4142.100 tank	NM	WS	2	E	*		F	
WS-14	American Standard	Yorkville EL	2876.100: 3701.100 bowl, 4142.100 tank	NM	WS	2	E		R	W	
WS-14	American Standard	Yorkville EL ADA	2878.100: 3703.100 bowl, 4142.100 tank	NM	WS	2	E	*	R	W	
5-510	Capizzi	Turbo Capizzi High Profile EL	0478 bowl, 1578 tank	500		2	E			F	
5-511	Capizzi	Turbo Capizzi Low Profile EL	0478 bowl, 1513 tank	400		2	E			F	
5-513	Capizzi	Turbo Capizzi Low Profile EL ADA	0441 bowl, 1513 tank	500		2	E	*		F	
11-038	Crane	EcoMiser EL	38340: 3824 bowl, 31500 tank	1,000		2	E			F	
11-039	Crane	EcoMiser EL	38350: 3825 bowl, 31500 tank	1,000		2	E			F	
11-040	Crane	EcoMiser EL ADA	38380: 3828 bowl, 31500 tank	1,000		2	E	*		F	
14-119	Crane	Economiser EL	3837: 3827100 bowl, 3612100 tank	600		2	E		R	F	
11-025	Crane	Economiser One Bigfoot EL	31885: 31125 bowl, 31612 tank	1,000	WS	2	E			F	
WS-11	Crane	Economiser One Bigfoot EL ADA	31888: 31128 bowl, 31612 tank	1,000	WS	2	E	*		F	
11-026	Crane	Economiser One Bigfoot RF	31884: 31124 bowl, 31612 tank	1,000	WS	2	R			F	
10-035	Crane	Economiser One EL	31945: 3825 bowl, 31612 tank	1,000		2	E			F	
10-034	Crane	Economiser One EL ADA	31948: 3828 bowl, 31612 tank	1,000		2	E	*		F	
10-037	Crane	Economiser One RF	31944: 3824 bowl, 31612 tank	1,000		2	R			F	

MaP Test Report No. (for internal use)	Make	Model Name	Model Number	MaP Flush Performance (grams of solid waste removed from the toilet in a SINGLE flush)	Certified to the U.S. EPA WaterSense Specification for High-Efficiency Toilets	KEY: Flush performance (MaP score)				1-piece or 2-piece model	Round Front (R) or Elongated (E) bowl	ADA-Comfort Height-Right Height Bowl	Rear Discharge	Floor-Mounted (F) OR Wall-Mounted (W)
						350 grams to 475 grams	500 grams and more	NM - Not measured for Maximum Performance - these WaterSense fixtures met the minimum 350 gram waste removal threshold, however.						
14-120	Crane	Economiser RF	3836: 3826100 bowl, 3612100 tank	600					2	R			R	F
9-009	Eljer	Power 1-G EL	091-7625: 131-7625 bowl; 141-7600 tank	800					2	E				F
9-010	Eljer	Power 1-G EL ADA	091-7675: 131-7675 bowl; 141-7600 tank	800					2	E	*			F
14-104	Gerber	Ultra Flush EL	EF-21-310: 21-374 bowl, EF-28-380 tank	800	WS				2	E			R	F
5-559	Gerber	Ultra Flush EL ADA	EF 21-318: 21-377 bowl, EF-28-380 tank	800	WS				2	E	*			F
5-563	Gerber	Ultra Flush EL ADA	EF-21-312: 21-372 bowl, EF-28-380 tank	800	WS				2	E	*			F
5-576	Gerber	Ultra Flush EL ADA	EF-21-314: 21-372 bowl, EF-28-384 tank	800	WS				2	E	*			F
5-584	Gerber	Ultra Flush EL ADA	EF-21-324: 21-372 bowl, EF-28-384 tank	800	WS				2	E	*			F
5-566	Gerber	Ultra Flush EL ADA (rear discharge)	EF-21-325: 21-375 bowl, EF-28-380 tank	800	WS				2	E	*	R		F
5-559	Gerber	Ultra Flush EL ADA (w/bedpan lugs)	EF-21-319: 21-329 bowl, EF-28-390 tank	800					2	E	*			F
6-615	Gerber	Ultra Flush RF	EF-21-302: 21-342 bowl, EF-28-380 tank	1,000	WS				2	R				F
6-619	Gerber	Ultra Flush RF	EF-21-304: 21-342 bowl, EF-28-384 tank	1,000	WS				2	R				F
12-036	Home Depot (by Niagara)	Power One EL	Home Depot SKU 385-195 - UPC Bar Code 732291231015 (Also available as Niagara N2310: 2310B bowl, 2310T tank)	1,000	WS				2	E				F
12-018	Kohler	Barrington Pressure Lite EL	K-3652: 4327 bowl, 4484 tank	800	WS				2	E			R	F
WS-12	Kohler	Fountainhead Power Lite EL ADA	K-3524 (one piece)	NM	WS				1	E	*			F
12-024	Kohler	San Raphael Pressure Lite EL ADA	K-3597 (one-piece)	600	WS				1	E	*			F
7-508	Kohler	Wellworth Pressure Lite EL	K-3531: 4303 bowl, 4484 tank	1,000	WS				2	E				F
7-509	Kohler	Highline Pressure Lite EL ADA	K-3519: 4304 bowl, 4484 tank	1,000	WS				2	E	*			F
12-027	Mansfield	Prestigio 4 EL	704 (one-piece)	950	WS				1	E				F
11-070	Mansfield	Quantum EL	144 bowl, 153 tank	900	WS				2	E	*	R		W
10-121	Mansfield	QuantumOne EL	147 bowl, 153 tank	1,000	WS				2	E				F
10-119	Mansfield	QuantumOne EL	149 bowl, 153 tank	1,000	WS				2	E			R	F
10-120	Mansfield	QuantumOne EL ADA	148 bowl, 153 tank	1,000	WS				2	E	*			F
10-122	Mansfield	QuantumOne RF	146 bowl, 153 tank	1,000	WS				2	R				F
12-036	Niagara	Power One EL	N2310: 2310B bowl, 2310T tank	1,000	WS				2	E				F
5-514	Peerless Pottery (by Capizzi)	Predator EL ADA	608 bowl, 1 tank	500					2	E	*			F

MaP Test Report No. (for internal use)	Make	Model Name	Model Number	MaP Flush Performance (grams of solid waste removed from the toilet in a SINGLE flush)	Certified to the U.S. EPA WaterSense Specification for High-Efficiency Toilets	1-piece or 2-piece model	Round Front (R) or Elongated (E) bowl	ADA-Comfort Height-Right Height Bowl	Rear Discharge	Floor-Mounted (F) OR Wall-Mounted (W)	KEY:
											Flush performance (MaP score)
											350 grams to 475 grams
											500 grams and more
											NM - Not measured for Maximum Performance - these WaterSense fixtures met the minimum 350 gram waste removal threshold, however.
5-512	Peerless Pottery (by Capizzi)	Predator Low Profile EL	606 bowl, 1 tank	400		2	E			F	
14-040	Pro-Flo (by Tynan for Ferguson)	None EL	PF1601: PF1601 bowl, PF1612 tank	900		2	E			F	
14-041	Pro-Flo (by Tynan for Ferguson)	None EL ADA	PF1603: PF1603 bowl, PF1612 tank	900		2	E	*		F	
14-031	Tynan Plumbing	None EL	4510: 7510 bowl, 1712 tank	900		2	E			F	
14-032	Tynan Plumbing	None EL ADA	4512: 7512 bowl, 1712 tank	900		2	E	*		F	
6-627	VitrA	Evergreen (formerly Arkitekt) EL ADA	5065 bowl, 5066 tank	500	WS	2	E	*		F	
5-504	Vortens-Lamosa	Tornado EL	3138 bowl, 3468 tank	700	WS	2	E			F	
8-553	Vortens-Lamosa	Tornado EL ADA	3134 bowl, 3468 tank	1,000	WS	2	E	*		F	
10-117 & 12-120	Western Pottery	Wrangler One EL	B432PF-1: 432 PF bowl, ULF-T4 tank	1,000		2	E			F	
6-634	Zurn	EcoVantage EL	Z5571: Z5570 bowl, Z5561 tank	800	WS	2	E			F	
6-638	Zurn	EcoVantage EL ADA	Z5561: Z5560 bowl, Z5561 tank	1,000	WS	2	E	*		F	
WS-12	Zurn	EcoVantage RF	Z5576: Z5575 bowl, Z5561 tank	NM	WS	2	R			F	

Notes: RF – Round-front toilet bowl

EL – Elongated-front toilet bowl

ADA-Meets bowl-height requirements of Americans with Disabilities Act; does NOT imply that fixture meets any other ADA requirement

NM - Not measured: WaterSense-certified fixtures that were not Maximum Performance (MaP) tested; these fixtures meet the minimum 350 gram waste removal threshold

WS - Compliance established by meeting the requirements of the U.S. EPA WaterSense specification for high-efficiency toilets; certified to WaterSense

G - Gallons per Flush

L - Litres per Flush