

Maximum Performance (MaP) of High-Efficiency Toilet Fixtures

Dual Flush HETs ONLY

Revisions to the previous 14th Edition listing are noted below with a blue block on the right margin →

| MaP Test Report No. (for internal use) | Make | Model Name | Model Number | MaP Flush Performance (grams of solid waste removed from the toilet in a SINGLE flush) | Meets Los Angeles specification (SPS) for water savings sustainability (adjustability maximum) | Certified to meet U.S. EPA WaterSense Specification | 1-piece or 2-piece model | Flush Valve-Flapper size (in.) | No flapper / Non-traditional flapper | Round Front (R) or Elongated (E) bowl | ADA-Comfort Height-Right Height Bowl | 1.6G (6L) gravity-fed full flush (exceptions noted) | Power OR Pressure-Assisted Full Flush at 1.6-G (6-L) | Rear Discharge (Back Outlet) | Floor-Mounted (F) OR Wall-Mounted (W) | KEY: | |
|---|--------------------------------------|--|--|--|--|---|--------------------------|--------------------------------|--------------------------------------|---------------------------------------|--------------------------------------|---|--|------------------------------|---------------------------------------|--|--|
| | | | | | | | | | | | | | | | | Flush performance (MaP column & score) | |
| | | | | | | | | | | | | | | | | | 250 grams to 475 grams |
| | | | | | | | | | | | | | | | | | 500 grams and more |
| | | | | | | | | | | | | | | | | | NM - Not measured for Maximum Performance - these WaterSense fixtures met the minimum 350 gram waste removal threshold, however. |
| 15-042 | American Standard | EcoFusion EL ADA | 3380.216: 3710.216 bowl, 4349.216 tank | 1,000 | WS | WS | 2 | 2 | | F | * | * | | | | F | |
| 10-126 | American Standard | FloWise Dual Flush EL | 2479.216 (this combination also sold as 2476.216 when with a slow-close seat): 3067 bowl, 4035.216 tank | 900 | WS | WS | 2 | 2 | * | F | | * | | | | F | |
| 12-112 | American Standard | FloWise Dual Flush EL (insulated tank) | SOLD IN 3 COMBINATIONS - 2479.516, 2779.516 and 2476.516: each combination with 3067 bowl, 4035.516 tank(lined) | 800 | WS | WS | 2 | 2 | | F | | * | | | | F | |
| 12-113 & 12-116 | American Standard | FloWise Dual Flush EL ADA | SOLD IN 4 COMBINATIONS - 2480.216, 2484.216, 2566.216 and 2778.516: each combination with 3073 bowl, 4035 tank. | 600 | WS | WS | 2 | | | F | * | * | | | | F | |
| 12-111 & 12-115 | American Standard | FloWise Dual Flush EL ADA (insulated tank) | SOLD IN 3 COMBINATIONS - 2480.516, 2484.516 and 2566.516: each combination with 3073 bowl, 4035.516 tank (lined) | 500 | WS | WS | 2 | 2 | | F | * | * | | | | F | |
| 15-135 | American Standard | FloWise Dual Flush RF | 2489.216: 3074.216 bowl, 4035.216 tank | 600 | WS | WS | 2 | - | * | R | | * | | | | F | |
| 15-136 | American Standard | FloWise Dual Flush RF (lined tank) | 2489.516: 3074.216 bowl, 4035.516 tank (lined) | 600 | WS | WS | 2 | - | * | R | | * | | | | F | |
| 14-132 | American Standard | H2Option Siphonic Dual Flush EL | 2887.216: 3706.216 bowl, 4339.216 tank | 1,000 | WS | WS | 2 | 2 | * | F | | * | | | | F | |
| 15-125 | American Standard | H2Option Siphonic Dual Flush EL (lined tank) | 2887.516: 3706.216 bowl, 4339.516 tank (lined) | 1,000 | WS | WS | 2 | - | * | F | | * | | | | F | |
| 14-131 | American Standard | H2Option Siphonic Dual Flush EL ADA | 2886.216: 3705.216 bowl, 4339.216 tank | 1,000 | WS | WS | 2 | 2 | * | F | * | * | | | | F | |
| 15-124 | American Standard | H2Option Siphonic Dual Flush EL ADA (lined tank) | 2886.516: 3705.216 bowl, 4339.516 tank (lined) | 1,000 | WS | WS | 2 | - | * | F | * | * | | | | F | |
| 14-133 | American Standard | H2Option Siphonic Dual Flush RF | 2889.216: 3708.216 bowl, 4339.216 tank | 1,000 | WS | WS | 2 | 2 | * | R | | * | | | | F | |
| 15-126 | American Standard | H2Option Siphonic Dual Flush RF (lined tank) | 2889.516: 3708.216 bowl, 4339.516 tank (lined) | 1,000 | WS | WS | 2 | - | * | R | | * | | | | F | |
| 7-535 | Aquadis | CT-A1200 RF | CT-A1200 (bowl & tank models nos. not identified) | 300 | SPS | | 2 | 2 | | R | | * | | | | F | |
| 10-055 | Aquadis | Tytane EL | TY350 (one piece) | 350 | SPS | | 1 | 2 | | E | | * | | | | F | |
| 14-030 | Aquasenses - Chongqing Swell Holding | Aquasenses RF | ES22114: ES2214 bowl, ES3214 tank | 350 | WS | WS | 2 | | | R | | * | | | | F | |
| 11-087 | Bolina | Italiana EL | 3031: 3031 bowl, 3031 tank | 400 | SPS | | 2 | 2 | | E | | * | | | | F | |
| WS-12 | Briggs | None EL | 4208: 4375 bowl, 4484 tank | NM | WS | WS | 2 | | | E | | * | | | | F | |
| WS-12 | Briggs | None RF | 4207: 4370 bowl, 4484 tank | NM | WS | WS | 2 | | | R | | * | | | | F | |
| 8-536 | Caroma | Adelaide 270 CC Cube RF | 834000 bowl, 814790 tank | 700 | SPS | WS | 2 | - | * | R | | * | | | | F | |
| 12-006 | Caroma | Adelaide 270 EH Cube RF ADA | 825500 bowl, 814790 tank | 700 | SPS | WS | 2 | - | * | R | * | * | | | | F | |
| 12-005 | Caroma | Adelaide 270 EH Standard RF ADA | 825500 bowl, 814328 tank | 700 | SPS | WS | 2 | - | * | R | * | * | | | | F | |
| 8-537 | Caroma | Adelaide 270 CC Standard RF | 834000 bowl, 814328 tank | 700 | SPS | WS | 2 | - | * | R | | * | | | | F | |

| MaP Test Report No. (for internal use) | Make | Model Name | Model Number | MaP Flush Performance (grams of solid waste removed from the toilet in a SINGLE flush) | Meets Los Angeles specification (SPS) for water savings sustainability (adjustability maximum) | Certified to meet U.S. EPA WaterSense Specification | 1-piece or 2-piece model | Flush Valve-Flapper size (in.) | No flapper / Non-traditional flapper | Round Front (R) or Elongated (E) bowl | ADA-Comfort Height-Right Height Bowl | 1.6G (6L) gravity-fed full flush (exceptions noted) | Power-OR Pressure-Assisted Full Flush at 1.6-G (6-L) | Rear Discharge (Back Outlet) | Floor-Mounted (F) OR Wall-Mounted (W) | KEY: |
|---|--------|---|----------------------------------|--|--|---|--------------------------|--------------------------------|--------------------------------------|---------------------------------------|--------------------------------------|---|--|------------------------------|---------------------------------------|--|
| | | | | | | | | | | | | | | | | Flush performance (MaP column & score) |
| | | | | | | | | | | | | | | | | 250 grams to 475 grams |
| | | | | | | | | | | | | | | | | 500 grams and more |
| | | | | | | | | | | | | | | | | NM - Not measured for Maximum Performance - these WaterSense fixtures met the minimum 350 gram waste removal threshold, however. |
| 10-113 | Caroma | Bondi 270 CC RF | 609159 bowl, 726350 tank | 600 | SPS | WS | 2 | - | * | R | | * | | | F | |
| 11-050 | Caroma | Bondi 270 EL | 609100 bowl, 726350 tank | 550 | WS | WS | 2 | - | * | E | | * | | | F | |
| 10-112 | Caroma | Bondi 270 EL ADA | 609120 bowl, 726350 tank | 900 | SPS | WS | 2 | - | * | E | * | * | | | F | |
| 11-049 | Caroma | Bondi 270 RF ADA | 609177 bowl, 726350 tank | 550 | WS | WS | 2 | - | * | E | * | * | | | F | |
| 10-110 | Caroma | Bondi 305 CC RF | 609151 bowl, 726350 tank | 450 | SPS | WS | 2 | - | * | R | | * | | | F | |
| 13-069 | Caroma | Bondi 305 EL | 609130 bowl, 726350 tank | 700 | WS | WS | 2 | - | * | E | | * | | | F | |
| 12-002 | Caroma | Brisbane 270 RF | 833900 bowl, 810266 tank | 700 | WS | WS | 2 | - | * | R | | * | | | F | |
| 8-538 | Caroma | Caravelle One-Piece RF ADA | 989668 | 800 | SPS | WS | 1 | - | * | R | * | * | | | F | |
| 9-032 | Caroma | Caravelle 270 EL | 609100 bowl, 629435 tank | 500 | SPS | WS | 2 | - | * | E | | * | | | F | |
| 7-525 | Caroma | Caravelle 270 EL ADA | 609120 bowl, 629435 tank | 800 | SPS | WS | 2 | - | * | E | * | * | | | F | |
| | Caroma | Caravelle 270 RF | 989760: 609159 bowl, 629435 tank | NM | WS | WS | 2 | - | * | R | | * | | | F | |
| | Caroma | Caravelle 270 RF ADA | 989770: 609177 bowl, 629435 tank | NM | WS | WS | 2 | - | * | R | * | * | | | F | |
| 7-526 | Caroma | Caravelle 305 EL | 609130 bowl, 629435 tank | 500 | SPS | WS | 2 | - | * | E | | * | | | F | |
| | Caroma | Caravelle 305 RF | 989680: 609151 bowl, 629435 tank | NM | WS | WS | 2 | - | * | R | | * | | | F | |
| 14-025 | Caroma | Caravelle One-Piece RF | 989646 | 700 | SPS | WS | 1 | - | * | R | | * | | | F | |
| 7-513 | Caroma | Colonial 270 RF | 605310 bowl, 625070 tank | 600 | SPS | WS | 2 | - | * | R | | * | | | F | |
| 12-004 | Caroma | Colonial 270 RF ADA | 605320 bowl, 625070 tank | 700 | SPS | WS | 2 | - | * | R | * | * | | | F | |
| 14-035 | Caroma | Profile Smart 305 RF (NOTE: 1.2g/4.5L for the full flush - 0.8g/3.0L for reduced flush) | 609151A bowl, 840420 tank | 800 | WS | WS | 2 | - | * | R | | 1.2g 4.5L | | | F | |
| 7-527 | Caroma | Reflections 270 EL | 609100 bowl, 629530 tank | 500 | SPS | | 2 | - | * | E | | * | | | F | |
| 7-524 | Caroma | Reflections 305 RF | 609151 bowl, 629530 tank | 600 | SPS | | 2 | - | * | R | | * | | | F | |
| 11-052 | Caroma | Royale 270 EL | 609100 bowl, 624530 tank | 800 | WS | WS | 2 | - | * | E | | * | | | F | |
| 7-514 | Caroma | Royale 270 EL ADA | 609120 bowl, 624530 tank | 800 | SPS | WS | 2 | - | * | E | * | * | | | F | |
| 7-528 | Caroma | Royale 270 RF | 609159 bowl, 624530 tank | 600 | WS | WS | 2 | - | * | R | | * | | | F | |
| 11-051 | Caroma | Royale 270 RF ADA | 609177 bowl, 624530 tank | 900 | WS | WS | 2 | - | * | E | * | * | | | F | |
| | Caroma | Royale 305 EL | 609130 bowl, 629530 tank | NM | WS | WS | 2 | - | * | E | | * | | | F | |
| | Caroma | Royale 305 RF | 609151 bowl, 624530 tank | NM | WS | WS | 2 | - | * | R | | * | | | F | |
| 11-055 | Caroma | Sydney 270 EL | 609100 bowl, 622320 tank | 500 | WS | WS | 2 | - | * | E | | * | | | F | |
| 8-533 | Caroma | Sydney 270 EL ADA | 609120 bowl, 622320 tank | 1,000 | SPS | WS | 2 | - | * | E | * | * | | | F | |
| 11-053 | Caroma | Sydney 270 RF | 609159 bowl, 622320 tank | 600 | WS | WS | 2 | - | * | E | | * | | | F | |
| 11-054 | Caroma | Sydney 270 RF ADA | 609177 bowl, 622320 tank | 600 | WS | WS | 2 | - | * | E | * | * | | | F | |

| MaP Test Report No. (for internal use) | KEY: Flush performance (MaP column & score) | | | MaP Flush Performance (grams of solid waste removed from the toilet in a SINGLE flush) | Meets Los Angeles specification (SPS) for water savings sustainability (adjustability maximum) | Certified to meet U.S. EPA WaterSense Specification | 1-piece or 2-piece model | Flush Valve-Flapper size (in.) | No flapper / Non-traditional flapper | Round Front (R) or Elongated (E) bowl | ADA-Comfort Height-Right Height Bowl | 1.6G (6L) gravity-fed full flush (exceptions noted) | Power OR Pressure-Assisted Full Flush at 1.6-G (6-L) | Rear Discharge (Back Outlet) | Floor-Mounted (F) OR Wall-Mounted (W) | | |
|---|--|--|--|--|--|---|--------------------------|--------------------------------|--------------------------------------|---------------------------------------|--------------------------------------|---|--|------------------------------|---------------------------------------|--|--|
| | Make | Model Name | Model Number | | | | | | | | | | | | | 250 grams to 475 grams | |
| | | | | | | | | | | | | | | | | 500 grams and more | |
| | | | | | | | | | | | | | | | | NM - Not measured for Maximum Performance - these WaterSense fixtures met the minimum 350 gram waste removal threshold, however. | |
| 10-115 | Caroma | Sydney 305 EL | 609130 bowl, 622320 tank | 500 | SPS | WS | 2 | - | * | E | | * | | | F | | |
| 10-114 | Caroma | Sydney 305 RF | 609151A bowl, 622320 tank | 1,000 | SPS | WS | 2 | - | * | R | | * | | | F | | |
| 12-093 | Caroma | Sydney Low Profile 270 EH EL ADA | 609120 bowl, 622330 tank | 550 | SPS | WS | 2 | - | * | E | * | * | | | F | | |
| 13-125 | Caroma | Sydney Low Profile 270 EL | 609100 bowl, 622330 tank | 550 | WS | WS | 2 | - | * | E | | * | | | F | | |
| 13-122 | Caroma | Sydney Low Profile 270 RF ADA | 609177 bowl, 622330 tank | 650 | WS | WS | 2 | - | * | R | * | * | | | F | | |
| 13-123 | Caroma | Sydney Low Profile 270 RF | 609159 bowl, 622330 tank | 550 | WS | WS | 2 | - | * | R | | * | | | F | | |
| 13-124 | Caroma | Sydney Low Profile 305 EL | 609130 bowl, 622330 tank | 550 | WS | WS | 2 | - | * | E | | * | | | F | | |
| 12-068 | Caroma | Sydney Low Profile 305 RF | 609151A bowl, 622330 tank | 500 | SPS | WS | 2 | - | * | R | | * | | | F | | |
| 14-037 | Caroma | Sydney Smart 270 EL (NOTE: 1.3g/4.9L full flush - 0.9g/3.4L reduced flush) | 609100 bowl, 622322 tank | 800 | WS | WS | 2 | - | * | E | | 1.2g 4.5L | | | F | | |
| 14-039 | Caroma | Sydney Smart 270 RF (NOTE: 1.3g/4.9L full flush - 0.9g/3.4L reduced flush) | 609159 bowl, 622322 tank | 800 | WS | WS | 2 | - | * | R | | 1.2g 4.5L | | | F | | |
| 13-121 | Caroma | Sydney Smart 270 EL ADA (NOTE: 1.28-gpf full flush - 0.8-gpf reduced flush) | 609120 bowl, 622322 tank | 800 | WS | WS | 2 | - | * | E | * | 1.2g 4.5L | | | F | | |
| 14-038 | Caroma | Sydney Smart 270 RF ADA (NOTE: 1.3g/4.9L full flush - 0.9g/3.4L reduced flush) | 609177 bowl, 622322 tank | 800 | WS | WS | 2 | - | * | R | * | 1.2g 4.5L | | | F | | |
| 14-036 | Caroma | Sydney Smart 305 EL (NOTE: 1.3g/4.9L full flush - 0.9g/3.4L reduced flush) | 609130 bowl, 622322 tank | 900 | WS | WS | 2 | - | * | E | | 1.2g 4.5L | | | F | | |
| 14-026 | Caroma | Sydney Smart Rear Outlet (NOTE: 1.28-gpf full flush - 0.8-gpf reduced flush) | 609450 bowl, 622322 tank | 900 | WS | WS | 2 | - | * | | | 1.2g 4.5L | | R | F | | |
| 11-116 & 12-003 | Caroma | Sydney Smart 305 RF (NOTE: 1.28-gpf full flush - 0.8-gpf reduced flush) | 609151A bowl, 622322 tank | 650 | WS | WS | 2 | - | * | R | | 1.2g 4.5L | | | F | | |
| 10-116 | Caroma | Walvit EL (ADA optional) | 604119 bowl, 227001 tank (concealed in-wall) | 500 | SPS | | 2 | - | * | E | * | * | | R | W | | |
| 15-003 | Ceralux | None RF | 221 bowl, 321 tank | 300 | | | 2 | 2 | | R | | * | | | F | | |
| WS-12 | Cerapure Industries | None EL ADA (one-piece) | C-3432D | NM | WS | WS | 1 | | * | E | * | * | | | F | | |
| WS-14 | Cerapure Industries | None EL ADA | CT-6008D | NM | WS | WS | 2 | | * | E | * | | | | F | | |
| 13-066 | Chelini | Marriot RF | B1215R/TDF1246: B1215R bowl, TDF1246 tank | 600 | SPS | WS | 2 | 2.5 | * | R | | * | | | F | | |
| 14-047 | Chelini | Marriot EL ADA | B1216E bowl, TDF1246 tank (lined tank) | 800 | SPS | WS | 2 | 2 | * | E | * | * | | | F | | |
| 14-080 | Chelini | Marriot EL | B1215E bowl, TDF1246 tank (lined tank) | 400 | SPS | WS | 2 | 2.5 | * | E | | * | | | F | | |
| WS-15 | Cobban Enterprises | None | B1215E bowl, TDF1246 tank (lined tank) | 400 | SPS | WS | 2 | 2.5 | * | E | | * | | | F | | |
| WS-15 | Cobban Enterprises | None | B1215R bowl, TDF1246 tank | 600 | SPS | WS | 2 | 2.5 | * | R | | * | | | F | | |
| WS-15 | Cobban Enterprises | None | B1216E bowl, TDF1246 tank (lined tank) | 800 | SPS | WS | 2 | 2 | * | E | * | * | | | F | | |
| 11-084 | Contrac | None RF | 4710BFZ (one piece with insulated tank) | 500 | SPS | | 1 | 2.5 | | R | | * | | | F | | |
| 11-085 | Contrac | None RF | 4710BFZU (one piece) | 600 | SPS | | 1 | 2.5 | | R | | * | | | F | | |

| MaP Test Report No. (for internal use) | KEY: Flush performance (MaP column & score) | | | MaP Flush Performance (grams of solid waste removed from the toilet in a SINGLE flush) | Meets Los Angeles specification (SPS) for water savings sustainability (adjustability maximum) | Certified to meet U.S. EPA WaterSense Specification | 1-piece or 2-piece model | Flush Valve-Flapper size (in.) | No flapper / Non-traditional flapper | Round Front (R) or Elongated (E) bowl | ADA-Comfort Height-Right Height Bowl | 1.6G (6L) gravity-fed full flush (exceptions noted) | Power OR Pressure-Assisted Full Flush at 1.6-G (6-L) | Rear Discharge (Back Outlet) | Floor-Mounted (F) OR Wall-Mounted (W) | | |
|---|--|---------------------------------|---|--|--|---|--------------------------|--------------------------------|--------------------------------------|---------------------------------------|--------------------------------------|---|--|------------------------------|---------------------------------------|--|--|
| | Make | Model Name | Model Number | | | | | | | | | | | | | 250 grams to 475 grams | |
| | | | | | | | | | | | | | | | | 500 grams and more | |
| | | | | | | | | | | | | | | | | NM - Not measured for Maximum Performance - these WaterSense fixtures met the minimum 350 gram waste removal threshold, however. | |
| 11-080 | Conrac | None RF | 4720BFZ combination (lined tank) | 600 | SPS | | 2 | 2 | | R | | * | | | F | | |
| 11-081 | Conrac | None RF | 4720BFZU combination | 550 | SPS | | 2 | 2 | | R | | * | | | F | | |
| 14-060 | Conrac | None RF (lined tank) | 5720BFZ: B5720BFZ bowl, T5720BFZ tank (lined) | 600 | SPS | WS | 2 | 2 | | R | | * | | | F | | |
| 14-070 | Conrac | Clint EL (1 piece - lined tank) | 5710BEZ (one-piece - lined tank) | 1,000 | SPS | WS | 1 | 2 | * | E | | * | | | F | | |
| 14-069 | Conrac | Clara (1 piece - lined tank) | 5710BLT (one-piece - lined tank) | 1,000 | SPS | WS | 1 | 2 | * | S | | * | | | F | | |
| 14-061 | Conrac | Colin EL (lined tank) | 5720BEZ: B5720BEZ bowl, T5720BEZ tank (lined) | 700 | SPS | WS | 2 | 2 | * | E | | * | | | F | | |
| 14-068 | Conrac | Colten EL ADA (lined tank) | 5720BIZ: B5720BIZ bowl, T5720BIZ tank (lined) | 800 | SPS | WS | 2 | 2 | * | E | * | * | | | F | | |
| WS-11 | Crane | Eco Galaxy/Cranada EL | 31008: 3372 bowl, 31590 tank | 500 | WS | WS | 2 | - | | E | | * | | | F | | |
| 13-014 | Crane | Eco Galaxy/Cranada EL ADA | 31009: 3815 bowl, 31590 tank | 800 | SPS | WS | 2 | 2 | | E | * | * | | | F | | |
| 13-013 | Crane | Eco Galaxy/Cranada EL ADA | 31069: 3815 bowl, 31593 tank (insulated) | 800 | SPS | WS | 2 | 2 | | E | * | * | | | F | | |
| WS-11 | Crane | Eco Galaxy/Cranada RF | 31007: 3352 bowl, 31590 tank | 500 | WS | WS | 2 | - | | R | | * | | | F | | |
| WS-11 | Crane | Eco Galaxy/Cranada RF | 31067: 3352 bowl, 31593 tank (insulated) | 600 | WS | WS | 2 | - | | R | | * | | | F | | |
| WS | Crane | Eco Saratoga Dual RF | 31970: 3352 bowl, 31960 tank | NM | WS | WS | 2 | | | R | | | | | F | | |
| WS-11 | Crane | Eco Saratoga EL | 31973: 3372 bowl, 31964 tank | 500 | WS | WS | 2 | | | E | | * | | | F | | |
| WS | Crane | Eco Saratoga EL | 31980: 3372 bowl, 31960 tank | NM | WS | WS | 2 | | | E | | | | | F | | |
| WS | Crane | Eco Saratoga EL | 31986: 3372 bowl, 31966 tank (insulated) | NM | WS | WS | 2 | | | E | | | | | F | | |
| 13-016 | Crane | Eco Saratoga EL ADA | 31983: 3815 bowl, 31964 tank | 600 | SPS | WS | 2 | 2 | | E | * | * | | | F | | |
| 13-015 | Crane | Eco Saratoga EL ADA | 31996: 3815 bowl, 31966 tank (insulated) | 600 | SPS | WS | 2 | 2 | | E | * | * | | | F | | |
| WS-11 | Crane | Eco Saratoga RF | 31972: 3352 bowl, 31964 tank | 600 | WS | WS | 2 | | | R | | * | | | F | | |
| WS | Crane | Eco Saratoga RF | 31976: 3352 bowl, 31966 tank (insulated) | NM | WS | WS | 2 | | | R | | | | | F | | |
| 11-028 | Crane | Ecomiser Bigfoot EL | 38345: 31125 bowl, 31500 tank | 1,000 | SPS | WS | 2 | - | * | E | | | * | | F | | |
| WS-11 | Crane | Ecomiser Bigfoot EL ADA | 38355: 31128 bowl, 31500 tank | 1,000 | WS | WS | 2 | - | * | E | * | | * | | F | | |
| WS | Crane | Ecomiser Dual EL | 38370: 3827 bowl, 31500 tank | NM | WS | WS | 2 | - | * | E | | | * | R | F | | |
| WS | Crane | Ecomiser Dual EL ADA | 38400: 3830 bowl, 31500 tank | NM | WS | WS | 2 | - | * | E | * | | * | R | F | | |
| 11-030 | Crane | Ecomiser One Bigfoot RF | 38335: 31124 bowl, 31500 tank | 1,000 | SPS | WS | 2 | | * | R | | | * | | F | | |
| WS-15 | Dolphin Plumbing Industrial | None | L1315E346 | NM | WS | WS | 1 | | | E | | | | | | | |
| WS-15 | Dolphin Plumbing Industrial | None | Z15R15 bowl, S17246 tank | NM | WS | WS | 2 | | | R | | | | | | | |
| WS-15 | Dolphin Plumbing Industrial | None | Z15E15 bowl, S17246 tank | NM | WS | WS | 2 | | | E | | | | | | | |
| WS-15 | Dolphin Plumbing Industrial | None | Z15E16 bowl, S17246 tank | NM | WS | WS | 2 | | | E | | | | | | | |
| 12-030 | Duravit | 2nd Floor (ADA optional) | 220509 bowl, 111.335 in-wall tank (Geberit) | 350 | SPS | WS | 2 | 2 | | S | * | * | | R | W | | |
| 12-032 | Duravit | Caro (ADA optional) | 015609 bowl, 111.335 in-wall tank (Geberit) | 350 | SPS | WS | 2 | 2 | | S | * | * | | R | W | | |

| MaP Test Report No. (for internal use) | Make | Model Name | Model Number | MaP Flush Performance (grams of solid waste removed from the toilet in a SINGLE flush) | Meets Los Angeles specification (SPS) for water savings sustainability (adjustability maximum) | Certified to meet U.S. EPA WaterSense Specification | 1-piece or 2-piece model | Flush Valve-Flapper size (in.) | No flapper / Non-traditional flapper | Round Front (R) or Elongated (E) bowl | ADA-Comfort Height-Right Height Bowl | 1.6G (6L) gravity-fed full flush (exceptions noted) | Power OR Pressure-Assisted Full Flush at 1.6-G (6-L) | Rear Discharge (Back Outlet) | Floor-Mounted (F) OR Wall-Mounted (W) | KEY: |
|---|----------|---------------------------------------|--|--|--|---|--------------------------|--------------------------------|--------------------------------------|---------------------------------------|--------------------------------------|---|--|------------------------------|---------------------------------------|--|
| | | | | | | | | | | | | | | | | Flush performance (MaP column & score) |
| | | | | | | | | | | | | | | | | 250 grams to 475 grams |
| | | | | | | | | | | | | | | | | 500 grams and more |
| | | | | | | | | | | | | | | | | NM - Not measured for Maximum Performance - these WaterSense fixtures met the minimum 350 gram waste removal threshold, however. |
| 8-544 | Duravit | Darling | 020709 bowl, 111.335 in-wall tank (Geberit) | 350 | SPS | WS | 2 | 2 | | R | * | * | | | R | W |
| 13-070 | Duravit | D-Code | 220909 bowl, used with in-wall tank | 500 | WS | WS | 2 | | | S | * | * | | | R | W |
| 12-031 | Duravit | Foster (ADA optional) | 017509 bowl, 111.335 in-wall tank (Geberit) | 350 | SPS | WS | 2 | 2 | | S | * | * | | | R | W |
| WS-13 | Duravit | Happy D | 017009 bowl, 091010 tank | NM | WS | WS | 2 | | | | | * | | | | F |
| 6-605 | Duravit | Happy D RF | 017009 bowl, 091000-05 tank | 600 | SPS | | 2 | 2 | | R | * | * | | | R | W |
| 6-604 | Duravit | Happy D Wallmount RF | 017109 bowl, 111.335 in-wall tank (Geberit) | 600 | SPS | WS | 2 | 2 | | R | * | * | | | R | W |
| 12-033 | Duravit | Starck 2 (ADA optional) | 016009 bowl, 111.335 in-wall tank (Geberit) | 350 | SPS | WS | 2 | 2 | | S | * | * | | | R | W |
| WS-13 | Duravit | Starck 3 | 012809 bowl, 092010 tank | NM | WS | WS | 2 | | | | | * | | | | F |
| 8-543 | Duravit | Starck 3 RF | 220009 bowl, 111.335 in-wall tank (Geberit) | 350 | SPS | WS | 2 | 2 | | R | * | * | | | R | W |
| WS-13 | Duravit | Starck X | 220409 bowl, used with in-wall tank | NM | WS | WS | 2 | | | S | * | * | | | R | W |
| WS-13 | Duravit | Vero | 211609 bowl, 090910 tank | NM | WS | WS | 2 | | | | | * | | | | F |
| WS-13 | Duravit | Vero | 211709 bowl, 109.304 in-wall tank (Geberit) | NM | SPS | WS | 2 | 2 | | S | | * | | | | F |
| 12-034 | Duravit | Vero (ADA optional) | 221709 bowl, 111.335 in-wall tank (Geberit) | 350 | SPS | WS | 2 | 2 | | S | * | * | | | R | W |
| 14-133D | Eljer | Somerville Dual Flush RF (siphonic) | 091-6100: 3708.416 bowl, 4339.416 tank | 1,000 | WS | WS | 2 | 2 | * | R | | * | | | | F |
| 12-017 | Foremost | AIO (All-In-One) EL ADA | AIO1000-E: AIOB1000-E bowl, AIOT1000 tank | 1,000 | WS | WS | 2 | - | * | E | * | | * | | | F |
| 12-016 | Foremost | AIO (All-In-One) RF ADA | AIO1000-R: AIOB1000-R bowl, AIOT1000 tank | 1,000 | WS | WS | 2 | - | * | R | * | | * | | | F |
| 14-073 | Foremost | HET EL ADA (one-piece) | HB-800-ADA (one-piece) | 1,000 | SPS | WS | 1 | 3 | * | E | * | * | | | | F |
| 8-539 | Foremost | Gemini Dual-Flush RF (lined tank) | TL-2005-*L: LL-2005 bowl, T-2005-*L tank (lined) | 800 | SPS | WS | 2 | 2 | * | R | | * | | | | F |
| 13-140 | Foremost | Genie EL (lined tank) | TL-2010E-*L, LL-2010E bowl, T-2010-*L tank (lined) | 700 | SPS | | 2 | 2 | * | E | | | | | | F |
| 9-044 & 13-147 | Foremost | Gemini Dual-Flush ADA | TL-2100-*L (one-piece) | 1,000 | SPS | WS | 1 | 2 | * | S | * | * | | | | F |
| 15-114 | Foremost | None EL ADA | A02-058777E: LL-777E bowl, T2-058 tank | 800 | SPS | | 2 | 3 | | E | * | * | | | | F |
| 15-116 | Foremost | None EL ADA | A02-158777E: LL-777E bowl, T2-158 tank | 850 | SPS | | 2 | 2 | | E | * | * | | | | F |
| 15-118 | Foremost | None RF ADA | A02-058777R: LL-777R bowl, T2-058 tank | 800 | SPS | | 2 | 3 | | R | * | * | | | | F |
| 15-119 | Foremost | None RF ADA | A02-158777R: LL-777R bowl, T2-158 tank | 900 | SPS | | 2 | 2 | | R | * | * | | | | F |
| 13-142 | Foremost | Regent RF | TL-5210-*L (one piece - lined tank) | 750 | SPS | WS | 1 | 2 | * | R | | | | | | F |
| 13-136 | Foremost | Benton EL (one-piece) | TL-7100-WL (one Piece) | 250 | SPS | | 1 | 2 | * | E | | * | | | | F |
| 11-001 | Foremost | Plaza | TL-7107-*L: LL-7107 bowl, T-7107 tank | 500 | WS | WS | 2 | 2.5 | * | S | | * | | | | F |
| 14-074 | Foremost | Odessa RF (one-piece with lined tank) | TL-8260-*L (one-piece with lined tank) | 800 | SPS | WS | 1 | 2 | * | S | | * | | | | F |
| 8-530 | Foremost | Moline EL | TL-8267-*L: LL-8267 bowl, T-8267 tank (lined) | 700 | SPS | WS | 2 | 2.5 | * | S | | * | | | | F |
| 13-141 | Foremost | Europa EL (one-piece with lined tank) | TL-8271E-*L (one-piece with lined tank) | 800 | SPS | WS | 1 | 2 | * | E | | | | | | F |

| MaP Test Report No. (for internal use) | Make | Model Name | Model Number | MaP Flush Performance (grams of solid waste removed from the toilet in a SINGLE flush) | Meets Los Angeles specification (SPS) for water savings sustainability (adjustability maximum) | Certified to meet U.S. EPA WaterSense Specification | KEY: Flush performance (MaP column & score) | | | | | | | | | |
|---|--|---|--|--|--|---|--|--------------------------------|--------------------------------------|---------------------------------------|--------------------------------------|---|--|------------------------------|---------------------------------------|---|
| | | | | | | | 1-piece or 2-piece model | Flush Valve-Flapper size (in.) | No flapper / Non-traditional flapper | Round Front (R) or Elongated (E) bowl | ADA-Comfort Height-Right Height Bowl | 1.6G (6L) gravity-fed full flush (exceptions noted) | Power OR Pressure-Assisted Full Flush at 1.6-G (6-L) | Rear Discharge (Back Outlet) | Floor-Mounted (F) OR Wall-Mounted (W) | |
| 13-134 | Foremost | Total Advantage EL (one-piece with lined tank) | TT-2000E-*L (one piece with lined tank) | 1,000 | SPS | WS | 1 | 2 | * | E | | | | | | F |
| 11-073 | Foremost | Total - RF | TT-2010-*L: LL-2010 bowl, T-2010 tank (lined) | 600 | WS | WS | 2 | 2.5 | * | R | | * | | | | F |
| 15-148 | Gerber | Maxwell Dual-Flush RF (12" rough-in - insulated tank) | DF-21-102: 21-152 bowl, DF-28-192 tank (insulated) | 600 | SPS | | 2 | 2 | | R | | * | | | | F |
| 15-149 | Gerber | Maxwell Dual-Flush RF (12" rough-in) | DF-21-102: 21-152 bowl, DF-28-190 tank | 600 | SPS | | 2 | 2 | | R | | * | | | | F |
| 15-150 | Gerber | Maxwell Dual-Flush EL (12" rough-in) | DF-21-112: 21-162 bowl, DF-28-190 tank | 500 | SPS | | 2 | 2 | | E | | * | | | | F |
| 15-151 | Gerber | Maxwell Dual-Flush EL (12" r.i.-insulated tank) | DF-21-112: 21-162 bowl, DF-28-192 tank (insulated) | 600 | SPS | | 2 | 2 | | E | | * | | | | F |
| 15-152 | Gerber | Maxwell Dual-Flush EL ADA (12' rough-in - insulated tank) | DF-21-118: 21-128 bowl, DF-28-192 tank (insulated) | 600 | SPS | | 2 | 2 | | E | * | * | | | | F |
| 14-099 | Gerber | Maxwell Dual-Flush EL ADA | DF-21-118: 21-128 bowl, DF-28-190 tank | 500 | SPS | WS | 2 | 2 | | E | * | * | | | | F |
| 14-103 | Gerber | Ultra Dual Flush EL | DF-21-310: 21-374 bowl, DF-28-380 tank | 1,000 | WS | WS | 2 | - | | E | | | * | R | | F |
| 15-RN | Gerber | Ultra Dual Flush EL | DF-21-312: 21-372 bowl, DF-28-380 tank | 1,000 | SPS | WS | 2 | - | | E | | | * | | | F |
| 15-RN | Gerber | Ultra Dual Flush EL | DF-21-314: 21-372 bowl, DF-28-384 tank | 1,000 | SPS | WS | 2 | - | | E | | | * | | | F |
| 15-RN | Gerber | Ultra Dual Flush EL ADA | DF 21-318: 21-377 bowl, DF-28-380 tank | 1,000 | SPS | WS | 2 | - | | E | * | | * | | | F |
| 15-RN | Gerber | Ultra Dual Flush EL ADA | DF-21-324: 21-377 bowl, DF-28-384 tank | 1,000 | SPS | WS | 2 | - | | E | * | | * | | | F |
| 15-RN | Gerber | Ultra Dual Flush EL ADA (rear discharge) | DF-21-325: 21-375 bowl, DF-28-380 tank | 1,000 | SPS | WS | 2 | - | | E | * | | * | R | | F |
| 15-158RN | Gerber | Ultra Dual Flush EL ADA (w/bedpan lugs) | DF 21-319: 21-329 bowl, DF-28-380 tank | 1,000 | SPS | | 2 | - | | E | * | | * | | | F |
| 6-616 | Gerber | Ultra Dual Flush RF | DF-21-302: 21-342 bowl, DF-28-380 tank | 1,000 | SPS | WS | 2 | | | R | | | * | | | F |
| 6-620 | Gerber | Ultra Dual Flush RF | DF-21-304: 21-342 bowl, DF-28-384 tank | 1,000 | SPS | WS | 2 | - | | R | | | * | | | F |
| WS-13 | Greentide - CE Union International | None | 6810H: X-6810H bowl, T-6810H tank | NM | WS | WS | 2 | | * | R | | | | | | F |
| WS-13 | Greentide - CE Union International | None | 6811H: X-6811H bowl, T-6811H tank | NM | WS | WS | 2 | | * | E | | | | | | F |
| WS-15 | Greentide - CE Union International | None EL (one-piece) | 0907 (one-piece) | NM | WS | WS | 1 | | | E | | | | | | F |
| WS-15 | Hali Industries | None EL (one-piece) | 0907 (one-piece) | NM | WS | WS | 1 | | | E | | | | | | F |
| WS-15 | Hali Industries | None RF | 2102 | NM | WS | WS | 2 | | | R | | | | | | F |
| WS-15 | Hali Industries | None EL | 2212 | NM | WS | WS | 2 | | | E | | | | | | F |
| 8-546 | HCG | None - EL | CS9001DF: C9001 bowl, S9002DF tank | 400 | SPS | | 2 | 2 | | E | | * | | | | F |
| 8-545 | HCG | None - RF | CS9002DF: C9002 bowl, S9002DF tank | 350 | SPS | | 2 | 2 | | R | | * | | | | F |
| 8-540 | Home Depot - Pegasus/Glacier Bay (by Foremost) | Dual-Flush RF | Home Depot SKU 131-926 | 800 | SPS | WS | 2 | - | | R | | * | | | | F |
| 14-043 | Home Depot - Glacier Bay | Glacier Bay Dual Flush EL ADA | N2316: N2316B bowl, N2316T tank (Also sold in Combined All-In-One package by Home Depot SKU 215-583 - UPC Code 732291231619) | 1,000 | SPS | WS | 2 | 2.5 | | E | * | * | | | | F |
| 12-076 | Kohler | Escale EL | K-3588: 4308 bowl, 4472 tank | 500 | WS | WS | 2 | | | E | | * | | | | F |

| MaP Test Report No. (for internal use) | Make | Model Name | Model Number | MaP Flush Performance (grams of solid waste removed from the toilet in a SINGLE flush) | Meets Los Angeles specification (SPS) for water savings sustainability (adjustability maximum) | Certified to meet U.S. EPA WaterSense Specification | 1-piece or 2-piece model | Flush Valve-Flapper size (in.) | No flapper / Non-traditional flapper | Round Front (R) or Elongated (E) bowl | ADA-Comfort Height-Right Height Bowl | 1.6G (6L) gravity-fed full flush (exceptions noted) | Power OR Pressure-Assisted Full Flush at 1.6-G (6-L) | Rear Discharge (Back Outlet) | Floor-Mounted (F) OR Wall-Mounted (W) | KEY: |
|---|-------------------------------|---|---|--|--|---|--------------------------|--------------------------------|--------------------------------------|---------------------------------------|--------------------------------------|---|--|------------------------------|---------------------------------------|--|
| | | | | | | | | | | | | | | | | Flush performance (MaP column & score) |
| | | | | | | | | | | | | | | | | 250 grams to 475 grams |
| | | | | | | | | | | | | | | | | 500 grams and more |
| | | | | | | | | | | | | | | | | NM - Not measured for Maximum Performance - these WaterSense fixtures met the minimum 350 gram waste removal threshold, however. |
| 13-063 | Kohler | Persuade EL | K-3654: 4322 bowl, 4419 tank | 600 | SPS | WS | 2 | 2.5 | | E | | * | | | | F |
| WS-15 | Kohler | Reve EL | K-3797 | NM | WS | WS | 1 | | | E | | | | | | F |
| 12-094 | Kohler | Saile EL | K-3564 (one piece) | 500 | SPS | WS | 1 | | | E | | * | | | | F |
| 7-545 | Kohler | San Raphael Power Lite EL ADA | K-3393 Power-Assisted | 1,000 | SPS | WS | 1 | - | * | E | * | | *-at 1.4-g | | | F |
| WS-15 | Kohler | San Raphael Power Lite EL ADA (one-piece) | K-3607 (one-piece) NOTE: This is a powered toilet with two flush volume settings. | NM | WS | WS | 1 | | | E | * | | | | | F |
| 9-051 | Kohler | Sterling Karsten Dual Force EL | 402028: 402026 bowl, 402023 tank | 400 | SPS | WS | 2 | 2 | * | E | | * | | | | F |
| 8-550 | Kohler | Sterling Karsten RF | 402025: 402021 bowl, 402023 tank | 800 | SPS | WS | 2 | 2 | * | R | | * | | | | F |
| 6-622 | Kohler | Sterling Rockton EL | 402027: 402026 bowl, 402022 tank | 350 | SPS | WS | 2 | - | * | E | | * | | | | F |
| WS | Kohler | Sterling Rockton RF | 402024: 402021 bowl, 402022 tank | NM | WS | WS | 2 | - | * | R | | * | | | | F |
| WS | Kohler | Sterling Stanton EL | 402040: 402030 bowl, 402031 tank | NM | WS | WS | 2 | - | * | E | | * | | | | F |
| 15-055 | Kohler | Strela EL ADA | K-3598 | NM | WS | WS | 2 | | | E | * | | | | | F |
| WS-15 | Laufen Bathrooms | Mylife (wall-mount) | 8.2094.6 wall-mount bowl used with Geberit 111.335 dual flush system | NM | WS | WS | 2 | | | | | | | | R | W |
| WS-15 | Laufen Bathrooms | Pro (wall-mount) | 2095.0: 8.2095.0 wall-mount bowl used with Geberit 111.335 dual flush system | NM | WS | WS | 2 | | | | | | | | R | W |
| WS-15 | Laufen Bathrooms | Pro (wall-mount - compact) | 2095.2: 8.2095.2 wall-mount bowl used with Geberit 111.335 dual flush system | NM | WS | WS | 2 | | | | | | | | R | W |
| 10-125 | Mansfield | EcoQuantum EL | 147 bowl, 119 tank | 1,000 | SPS | WS | 2 | - | | E | | | * | | | F |
| 10-118 | Mansfield | EcoQuantum EL | 149 bowl, 119 tank | 550 | SPS | WS | 2 | - | | E | | | * | | R | F |
| 10-123 | Mansfield | EcoQuantum EL ADA | 148 bowl, 119 tank | 1,000 | SPS | WS | 2 | - | | E | * | | * | | | F |
| 10-124 | Mansfield | EcoQuantum RF | 146 bowl, 119 tank | 1,000 | SPS | WS | 2 | - | | R | | | * | | | F |
| 11-068 | Mansfield | EcoQuantum - EL | 144 bowl, 119 tank | 1,000 | SPS | WS | 2 | - | | E | * | | * | | R | W |
| 14-024 | Mansfield/Colceramica | Enso EL ADA | 177 bowl, 178 tank | 800 | SPS | WS | 2 | 2.5 | | E | * | * | | | | F |
| 14-043 | Niagara | Dual Flush EL ADA | N2316: N2316B bowl, N2316T tank (Also sold at Home Depot in a Combination All-In-One package as HD SKU 215-583 - UPC Bar Code 732291231619) | 1,000 | SPS | WS | 2 | 2.5 | | E | * | * | | | | F |
| 14-105 | Niagara | Dual Flush EL ADA | N2328: N2328B bowl, N2328T tank | 1,000 | SPS | WS | 2 | 2.5 | | E | * | * | | | | F |
| WS-13 | OPS - Original Pacific Supply | None EL | T/X-6688E: T-6688E bowl, X-6688 tank | NM | WS | WS | 2 | | | E | | * | | | | F |
| WS-13 | OPS - Original Pacific Supply | None EL ADA | T/X-6688H: T-6688H bowl, X-6688 tank | NM | WS | WS | 2 | | | E | * | * | | | | F |
| WS-13 | OPS - Original Pacific Supply | None RF | T/X-6688: T-6688 bowl, X-6688 tank | NM | WS | WS | 2 | | | R | | * | | | | F |
| WS-15 | OPS - Original Pacific Supply | None RF | T/X-66892: T-66892 bowl, X-66892 tank | NM | WS | WS | 2 | | | R | | | | | | F |
| WS-15 | OPS - Original Pacific Supply | None EL | T/X-66892E: T-66892E bowl, X-66892 tank | NM | WS | WS | 2 | | | E | | | | | | F |
| WS-15 | OPS - Original Pacific Supply | None EL | T/X-66892H: T-66892H bowl, X-66892 tank | NM | WS | WS | 2 | | | E | | | | | | F |

| MaP Test Report No. (for internal use) | Make | Model Name | Model Number | MaP Flush Performance (grams of solid waste removed from the toilet in a SINGLE flush) | Meets Los Angeles specification (SPS) for water savings sustainability (adjustability maximum) | Certified to meet U.S. EPA WaterSense Specification | 1-piece or 2-piece model | | Flush Valve-Flapper size (in.) | No flapper / Non-traditional flapper | Round Front (R) or Elongated (E) bowl | ADA-Comfort Height-Right Height Bowl | 1.6G (6L) gravity-fed full flush (exceptions noted) | Power OR Pressure-Assisted Full Flush at 1.6-G (6-L) | Rear Discharge (Back Outlet) | Floor-Mounted (F) OR Wall-Mounted (W) |
|---|------------------------|--|---|--|--|---|--------------------------|-----|--------------------------------|--------------------------------------|---------------------------------------|--------------------------------------|---|--|------------------------------|---------------------------------------|
| | | | | | | | 1 | 2 | | | | | | | | |
| | | KEY: Flush performance (MaP column & score) | | | | | | | | | | | | | | |
| | | 250 grams to 475 grams | | | | | | | | | | | | | | |
| | | 500 grams and more | | | | | | | | | | | | | | |
| | | NM - Not measured for Maximum Performance - these WaterSense fixtures met the minimum 350 gram waste removal threshold, however. | | | | | | | | | | | | | | |
| 13-005 | ProCon Solutions | None | CO-1011 EL (one-piece) | 250 | | | 1 | 2 | | | E | | * | | | F |
| 13-062 | Price Pfister (by HCG) | None EL ADA | VTP-E21: C-1003 bowl, S-1004 tank | 1,000 | SPS | WS | 2 | 3 | | | E | * | * | | | F |
| 13-115 | Price Pfister | None EL | VTP-E51: C-5518 bowl, S-5518 tank | 1,000 | SPS | | 2 | 3 | | | E | | * | | | F |
| 15-026 | Price Pfister | None RF | VTP-E40 (one piece) | 600 | SPS | | 1 | 3 | | | R | | * | | | F |
| 15-084 | Price Pfister | None EL | VTP-E11W | 1,000 | | | 2 | 3 | | | E | | * | | | F |
| 15-051 | Price Pfister | None EL | VTP-E20W (one-piece) | 600 | SPS | | 1 | 3 | | | E | | * | | | F |
| 13-061 | Price Pfister | None EL ADA | VTP-E31: C-1003 bowl, S-1003 tank | 1,000 | SPS | | 2 | 3 | | | E | * | * | | | F |
| 11-066 | PROFLO | Cascade EL | PF9301 bowl; PF9312 tank | 400 | SPS | WS | 2 | 2 | | | E | | * | | | F |
| 11-065 | PROFLO | Cascade EL ADA | PF9303 bowl; PF9312 tank | 450 | SPS | WS | 2 | 2 | | | E | * | * | | | F |
| 11-067 | PROFLO | Cascade RF | PF9300 bowl; PF9312 tank | 500 | SPS | WS | 2 | 2 | | | R | | * | | | F |
| WS-12 | PROFLO | None EL | PF9201 bowl; PF9212 tank | NM | WS | WS | 2 | | | | E | | * | | | F |
| WS-12 | PROFLO | None RF | PF9200 bowl; PF9212 tank | NM | WS | WS | 2 | | | | R | | * | | | F |
| 12-015 | Quality Craft | Alexis HET Dual Flush Toilet in Box EL ADA | 30014K: 3001 bowl, 3004 tank (insulated) | 900 | SPS | WS | 2 | 3 | | | E | * | * | | | F |
| 12-011 | Quality Craft | None - EL ADA | 3001/3004 (insulated tank) | 900 | SPS | | 2 | 3 | | | E | * | * | | | F |
| 9-003 | RAK Ceramics | Venice EL | VN03 bowl, VN10 tank | 500 | SPS | | 2 | 2 | | | E | | * | | | F |
| 15-044 | Roca | Happening Dual-Flush ADA | 65361 bowl, 65570 tank | 800 | SPS | | 2 | 2.5 | | | S | * | * | | | F |
| 15-045 | Roca | Hall Dual-Flush | 67361 bowl, 67570 tank | 850 | SPS | | 2 | 2.5 | | | S | * | * | | | F |
| 15-085 | Roca | Dama Senso ADA | 59361 bowl, 59570 tank | 800 | SPS | | | 2.5 | | | S | * | * | | | F |
| 14-045 | Roca | Johnson Suisse, Cottage EL ADA (one-piece) | No number | 400 | SPS | | 1 | 2.5 | | | E | * | 1.25g 4.7L | | | F |
| 13-141 | Rona | Europa EL | SKU#7369129 (Foremost #TL-8271E-WL) | 800 | SPS | | 1 | 2 | * | | E | | | | | F |
| 9-044 & 13-147 | Rona | Gemini Dual Flush ADA | SKU#7369068 (Foremost # TL-2100-*L) | 1,000 | SPS | WS | 1 | 2 | * | | S | * | * | | | F |
| 8-539 | Rona | Gemini Dual Flush RF | SKU# 7369067 (Foremost #TL-2005-*L) | 800 | SPS | | 2 | 2 | * | | R | | * | | | F |
| 8-530 | Rona | Rona Collection | SKU#2003354 (Foremost #TL-8267-WL) | 700 | SPS | | 2 | 2.5 | * | | S | | * | | | F |
| WS-15 | Seasons (HD Supply) | None EL | 564-852 bowl, 564-851 tank | NM | WS | WS | 2 | | | | E | | | | | |
| 12-017 | Seasons (HD Supply) | Dual Flush EL ADA | SE 10056 bowl, SE10055 tank (Same as Foremost AIOB1000-E bowl, AIOB1000 tank; also HD Supply Facilities Maint Nos. 564852 and 564851, respectively) | 1,000 | WS | WS | 2 | | * | | E | * | * | | | F |
| 14-030 | Swell Holding | Aquasenses RF | ES22114: ES2214 bowl, ES3214 tank | 350 | WS | WS | 2 | | | | R | | | | | F |
| 15-RN | Toto | Aquia EL | CST414M: CT414 bowl, ST413M tank | 800 | SPS | WS | 2 | 2 | | | E | | * | | | F |
| 12-082 | Toto | Aquia II EL | CST416M: CT416 bowl, ST416M tank | 500 | WS | WS | 2 | 2.5 | | | E | | | | | F |

| MaP Test Report No. (for internal use) | Make | Model Name | Model Number | MaP Flush Performance (grams of solid waste removed from the toilet in a SINGLE flush) | Meets Los Angeles specification (SPS) for water savings sustainability (adjustability maximum) | Certified to meet U.S. EPA WaterSense Specification | 1-piece or 2-piece model | Flush Valve-Flapper size (in.) | No flapper / Non-traditional flapper | Round Front (R) or Elongated (E) bowl | ADA-Comfort Height-Right Height Bowl | 1.6G (6L) gravity-fed full flush (exceptions noted) | Power OR Pressure-Assisted Full Flush at 1.6-G (6-L) | Rear Discharge (Back Outlet) | Floor-Mounted (F) OR Wall-Mounted (W) |
|---|-------------------------------|------------------------------|--|--|--|---|--------------------------|--------------------------------|--------------------------------------|---------------------------------------|--------------------------------------|---|--|------------------------------|---------------------------------------|
| | | | | | | | | | | | | | | | |
| | | | 250 grams to 475 grams | | | | | | | | | | | | |
| | | | 500 grams and more | | | | | | | | | | | | |
| | | | NM - Not measured for Maximum Performance - these WaterSense fixtures met the minimum 350 gram waste removal threshold, however. | | | | | | | | | | | | |
| WS-14 | WaterRidge-Milim G&G Ceramics | None EL | C21075C: C531082 bowl, C600137 tank | NM | WS | WS | 2 | | | E | | * | | | F |
| 12-040 | Western Pottery | Environmental Dual Flush EL | B812 DF bowl, T8-ULF-DF tank | 550 | SPS | WS | 2 | 2 | | E | | * | | | F |
| 15-049 | Western Pottery | None EL ADA | 817DF: 817 bowl, T8-DF tank | 800 | SPS | WS | 2 | 2.5 | | E | * | | | | F |
| 6-637 | Zurn | EcoVantage Dual Flush EL | Z5572: Z5570 bowl, Z5562 tank | 800 | SPS | WS | 2 | - | * | E | | | * | | F |
| 6-639 | Zurn | EcoVantage Dual Flush EL ADA | Z5562: Z5560 bowl, Z5562 tank | 1,000 | SPS | WS | 2 | - | * | E | * | | * | | F |
| WS-12 | Zurn | EcoVantage Dual Flush RF | Z5577: Z5575 bowl, Z5562 tank | NM | WS | WS | 2 | | | R | | | * | | F |
| WS-15 | Villeroy & Boch | Sentique EL | 5625 11 bowl, 5722 U1 tank | NM | WS | WS | 2 | | | E | | | | | F |

Notes: RF – Round-front toilet bowl
 EL – Elongated-front toilet bowl
 S - Special bowl design

ADA-Meets bowl-height requirements of Americans with Disabilities Act; does NOT imply that fixture meets any other ADA requirements.

NM - Not measured: WaterSense-certified fixtures that were not Maximum Performance (MaP) tested; these fixtures meet the minimum 350 gram waste removal threshold.

WS - Compliance established by meeting the requirements of the U.S. EPA WaterSense specification for high-efficiency toilets; certified to WaterSense

SPS - Qualified to the Los Angeles Supplementary Purchase Specification for flush volume adjustability

G - Gallons per Flush

L - Litres per Flush

RN - Renewed Listing